



The Pumps with Nine Lives

Model: [1051C](#)
15 FRAME FLUSHED PLUNGER PUMP

Specs

Max Flow:	10 gpm
Min Pressure:	100 psi
Max Pressure:	2200 psi
Inlet Port Size:	3/4"NPT
Discharge Port Size:	1/2"NPT
RPM:	968
Drive Type(s):	Belt
Material:	Stainless Steel (SS)

Description:

This is a triplex [three plunger rods] positive displacement, reciprocating, plunger pump, constructed of 316SS manifold, 316SS valve assemblies, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings. The C indicates the special flushed Inlet Manifold that permits an external flush liquid providing added cooling for hi-temp liquids and added lubrication for low-lubricity liquids such as DI water.

[Datasheet: 1050-1051- 1051C- 1051D -1057 Data Sheet](#)

[Service Manual: 5-15 Frame Plunger Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator

[7013.100](#)

SS Pressure Regulator

Relief / Pop-Off Valve



[9941](#)

Pop-Off Valve

[7036](#)

SS Pressure Relief Valve

Pressure Gauge



[6097](#)

Pressure Gauge

Pulsation Dampener



[6031](#)

Prrrrr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[711500](#)

Captive Acceleration Tube


Inlet Filter



[7105.5](#)

Inlet Filter


Flexible Inlet Hose



[990849](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990852](#)

Flexible Discharge Hose

LPS Monitors



[30664](#)

LPS Monitor



[30664.120AC](#)

LPS Monitor

Other



[34334](#)

Oil Drain Kit