



The Pumps with Nine Lives



Model: [1530](#) 15 FRAME PLUNGER PUMP

Specs

Max Flow:	15.6 gpm
Min Pressure:	100 psi
Max Pressure:	1500 psi
Inlet Port Size:	1"NPT
Discharge Port Size:	3/4"NPT
RPM:	1450
Drive Type(s):	Belt
Material:	Brass (BB)

Description:

This is a triplex (three plunger rods) positive displacement, reciprocating, plunger pump, constructed of forged brass manifold, 304SS valve assemblies, solid ceramic plungers and standard NBR (Buna-N) seals and o-rings. These higher capacity plunger pumps are suitable for multi-gun and multi-nozzle, high pressure systems. [see also 316SS models]

Datasheet: [1530-1531 Data Sheet](#)

Service Manual: [15-25 Frame Plunger Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator



[7022](#)

Pressure Regulator



[7013.100](#)

SS Pressure Regulator

Relief / Pop-Off Valve



[9940](#)

Pop-Off Valve

Pressure Gauge



[6088](#)

Pressure Gauge

Pulsation Dampener



[6010](#)

Prrrrr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[714500](#)

Captive Acceleration Tube


Inlet Filter



[7106.6](#)

Inlet Filter


Flexible Inlet Hose



[990842](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990832](#)

Flexible Discharge Hose

LPS Monitors



[30664](#)

LPS Monitor



[30664.120AC](#)

LPS Monitor

Other



[34334](#)

Oil Drain Kit