



**Model: [1540E](#)**  
**15 FRAME PLUNGER PUMP**

**Specs**

<b>Max Flow:</b>	18 gpm
<b>Min Pressure:</b>	100 psi
<b>Max Pressure:</b>	1200 psi
<b>Inlet Port Size:</b>	1"NPT
<b>Discharge Port Size:</b>	3/4"NPT
<b>RPM:</b>	1100
<b>Drive Type(s):</b>	Belt
<b>Material:</b>	Brass (BB)

**Description:**

This is a high performance mid-size triplex (three plunger rods) positive displacement, reciprocating, plunger pump. It has a forged brass manifold, 304SS valve assemblies, concentric, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings. It also features a durable blue 2 mil epoxy paint treatment on the crankcase, rear cover and bearing covers and a special Liquid Gasket between the crankcase and manifold to seal out moisture. This high capacity plunger pump is suitable for automatic car wash systems, multi-gun and multi-nozzle cleaning, and multi-drop high pressure cleaning systems.

**Datasheet:** [1540E-1540EC-1541 Data Sheet](#)

**Service Manual:** [15-25 Frame Plunger Service Manual](#)

**Accessories:**

**Oil**



[6107](#)

Crankcase Oil

**Regulator**

[7022](#)

Pressure Regulator

**Relief / Pop-Off Valve**



[9940](#)

Pop-Off Valve

**Pressure Gauge**



[6088](#)

Pressure Gauge

**Pulsation Dampener**



[6010](#)

Prrrrr-O-Lator-Rechg-NBR

**Captive Acceleration Tube**



[714500](#)

Captive Acceleration Tube


**Inlet Filter**



[71066](#)

Inlet Filter


#### Flexible Inlet Hose



[990842](#)

Flexible Inlet Hose

#### Flexible Discharge Hose



[990832](#)

Flexible Discharge Hose

#### LPS Monitors



[30664](#)

LPS Monitor



[30664.120AC](#)

LPS Monitor

#### Other



NO IMAGE  
AVAILABLE

[34334](#)

Oil Drain Kit