

Model: [1541](#)
15 FRAME PLUNGER PUMP

Specs

Max Flow:	18 gpm
Min Pressure:	100 psi
Max Pressure:	1200 psi
Inlet Port Size:	1"NPT
Discharge Port Size:	3/4"NPT
RPM:	1100
Drive Type(s):	Belt
Material:	N/A

Description:

This is a high performance mid-size triplex (three plunger rods) positive displacement, reciprocating, plunger pump. It has a stainless steel manifold, 316SS valve assemblies, concentric, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings.

Datasheet: [1540E-1540EC-1541 Data Sheet](#)

Service Manual: [15-25 Frame Plunger Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator



[7022.100](#)

SS Pressure Regulator

Relief / Pop-Off Valve



[9941](#)

Pop-Off Valve



[7034](#)

SS Pressure Relief Valve

Pressure Gauge



[6097](#)

Pressure Gauge

Pulsation Dampener



[6014](#)

Prrrrr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[714500](#)

Captive Acceleration Tube

Inlet Filter



[7106.6](#)

Inlet Filter


Flexible Inlet Hose



[990848](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990854](#)

Flexible Discharge Hose

LPS Monitors



[30664](#)

LPS Monitor



[30664.120AC](#)

LPS Monitor

Other



[34334](#)

Oil Drain Kit