



**Model: [1560](#)
15 FRAME PLUNGER PUMP**

Specs

Max Flow:	8 gpm
Min Pressure:	100 psi
Max Pressure:	4000 psi
Inlet Port Size:	3/4"NPT
Discharge Port Size:	1/2"NPT
RPM:	1140
Drive Type(s):	Belt
Material:	Brass (BB)

Description:

This is a mid-size, high pressure, triplex (three plunger rods) positive displacement, reciprocating, plunger pump. It has a heavy-duty, forged brass manifold, easy to service 304SS stacked valve assembly, concentric, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings. This 4000 PSI plunger pump is suitable for high pressure blasting, sewer cleaning and jetting and industrial heavy equipment wash down systems.

Datasheet: [1560 Data Sheet](#)

Service Manual: [15-25 Frame Plunger Service Manual](#)

Accessories:


Oil



[6107](#)

Crankcase Oil

Regulator



[7014](#)

Pressure Regulator

Relief / Pop-Off Valve



[9940](#)

Pop-Off Valve

Pressure Gauge



[6089](#)

Pressure Gauge

Pulsation Dampener



[6011](#)

Prrrrr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[711500](#)

Captive Acceleration Tube

Inlet Filter



[7105.5](#)

Inlet Filter


Flexible Inlet Hose



[990841](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990857](#)

Flexible Discharge Hose

LPS Monitors



[30664](#)

LPS Monitor



[30664.120AC](#)

LPS Monitor

Other



[34334](#)

Oil Drain Kit