



The Pumps with Nine Lives

**Model: [1810K](#)**  
**18 FRAME BLOCK-STYLE PLUNGER PUMP**



**Specs**

Max Flow:	3 gpm
Min Pressure:	100 psi
Max Pressure:	10000 psi
Inlet Port Size:	1/2"NPT(F)
Discharge Port Size:	3/8"NPT(F)
RPM:	1500
Drive Type(s):	Belt
Material:	Stainless Steel (S)

**Description:**

This is a triplex (three plunger rods) positive displacement, reciprocating, plunger pump, constructed of 304S Heat Treated stainless steel block-style manifolds, 304 stainless steel valve assemblies with ceramic balls, ceramic plungers, acetal seals, UHMW V-Packings and NBR o-rings. The pump features a low unswept volume (minimal un-evacuated liquid remains in the pumping chamber) resulting in maximum volumetric efficiency. This pump is designed for hydro blasting, hydrostatic testing and injection.

**Datasheet:** [1810-1810K Data Sheet](#)

**Service Manual:** [1810, 1810K Service Manual](#)

**Accessories:**

**Regulator**



[7720](#)

Pressure Regulator

**Pressure Gauge**



[6081](#)

Pressure Gauge

**Pulsation Dampener**



[701537](#)

Pulsation Dampener - Rebuild FPM



[701610](#)

Pulsation Dampener - Rebuild NBR



[701507](#)

Pulsation Dampener - Rebuild NBR



[701527](#)

Pulsation Dampener - Rebuild EPDM

## Captive Acceleration Tube



[711502](#)

Adapter-C.A.T.



[711500](#)

Captive Acceleration Tube

## Inlet Filter



[7104](#)


Inlet Filter



[7104.4](#)

Inlet Filter

## Flexible Inlet Hose



[990845](#)

Flexible Inlet Hose