



The Pumps with Nine Lives



**Model: [230](#)
3 FRAME PLUNGER PUMP**

Specs

Max Flow:	2.3 gpm
Min Pressure:	100 psi
Max Pressure:	1500 psi
Inlet Port Size:	0.5
Discharge Port Size:	0.37
RPM:	1725
Drive Type(s):	Belt
Material:	Brass (BB)

Description:

This is a triplex [three plunger rods] positive displacement, reciprocating, plunger pump, constructed of forged brass manifolds, 304 SS valve assemblies, solid ceramic plungers and standard NBR [Bunea-N] seals and o-rings. The 1725 RPM permits a close coupled installation using a bell housing and flexible coupling or direct-drive motor-pump unit.

[Datasheet: 230-240-270 Data Sheet](#)

[Service Manual: 3 Frame Plunger Service Manual](#)

Accessories:

Oil

	6107	Crankcase Oil
---	----------------------	---------------

Regulator

	7002	Pressure Regulator
---	----------------------	--------------------

Unloader

	7500S	Pressure Sensitive Regulating Unloader
---	-----------------------	--

Relief / Pop-Off Valve

	33962	Pop-Off Valve
---	-----------------------	---------------

Pressure Gauge

	6088	Pressure Gauge
---	----------------------	----------------

Pulsation Dampener

	6029	Pmmr-O-Lator-Rechg-NBR
---	----------------------	------------------------

Captive Acceleration Tube



[711500](#)

Captive Acceleration Tube

Inlet Filter



[7104.4](#)

Inlet Filter


Flexible Inlet Hose



[990840](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990836](#)

Flexible Discharge Hose

Other



[34334](#)

Oil Drain Kit