



The Pumps with Nine Lives

## Model: [231](#) 3 FRAME PLUNGER PUMP



### Specs

Max Flow:	2.3 gpm
Min Pressure:	100 psi
Max Pressure:	1500 psi
Inlet Port Size:	0.5
Discharge Port Size:	0.37
RPM:	1725
Drive Type(s):	Belt
Material:	Stainless Steel (SS)

### Description:

This is a triplex (three plunger rods) positive displacement, reciprocating, plunger pump, constructed of 316 SS manifolds, 316 SS valve assemblies, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings. The 1725 RPM permits a close coupled installation using a bell housing and flexible coupling or direct-drive motor-pump unit.

Datasheet: [231-237-241-247-271-277 Data Sheet](#)

Service Manual: [3 Frame Plunger Service Manual](#)

### Accessories:

#### Oil



[6107](#)

Crankcase Oil

#### Regulator



[7002.100](#)

SS Pressure Regulator

#### Unloader



[7501](#)

SS Pressure Sensitive Regulating Unloader

#### Relief / Pop-Off Valve



[9961](#)

SS Pop-Off Valve



[7501.100](#)

SS Pressure Relief Valve

#### Pressure Gauge



[6097](#)

Pressure Gauge

#### Pulsation Dampener



[6031](#)

Prrrrr-O-Lator-Rechg-NBR

## Captive Acceleration Tube



[711500](#)

Captive Acceleration Tube

## Inlet Filter



[7104.4](#)

Inlet Filter

## Flexible Inlet Hose



[990845](#)

Flexible Inlet Hose

## Flexible Discharge Hose



[990859](#)

Flexible Discharge Hose

## Other



[34334](#)

Oil Drain Kit