

**Model: [2530](#)
25 FRAME PLUNGER PUMP**

Specs

Max Flow:	25 gpm
Min Pressure:	100 psi
Max Pressure:	1000 psi
Inlet Port Size:	1.25
Discharge Port Size:	0.75
RPM:	1025
Drive Type(s):	Belt
Material:	N/A

Description:

This is a triplex (three plunger rods) positive displacement, reciprocating, plunger pump, constructed of forged brass manifolds, 316SS valve assemblies, solid ceramic plungers and standard NBR (Buna-N) seals and o-rings. These higher capacity plunger pumps are suitable for multi-gun and multi-nozzle and industrial high pressure systems. [see also 316SS models]

Datasheet: [2530-2530E-2531-2537 Data Sheet](#)

Service Manual: [25 Frame Plunger Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator



[7022](#)

Pressure Regulator



[7031](#)

Pressure Regulator

Relief / Pop-Off Valve



[9940](#)

Pop-Off Valve

Pressure Gauge



[6088](#)

Pressure Gauge

Pulsation Dampener



[6010](#)

Prrrrr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[714500](#)

Captive Acceleration Tube

Inlet Filter



[7107.7](#)

Inlet Filter


Flexible Inlet Hose



[990843](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990837](#)

Flexible Discharge Hose

LPS Monitors



[30290](#)

LPS Monitor



[30290.120AC](#)

LPS Monitor

Other



[34334](#)

Oil Drain Kit