



The Pumps with Nine Lives

**Model: [2531](#)**  
**25 FRAME PLUNGER PUMP**

**Specs**

<b>Max Flow:</b>	25 gpm
<b>Min Pressure:</b>	100 psi
<b>Max Pressure:</b>	1000 psi
<b>Inlet Port Size:</b>	1.25
<b>Discharge Port Size:</b>	0.75
<b>RPM:</b>	1025
<b>Drive Type(s):</b>	Belt
<b>Material:</b>	Stainless Steel (SS)

**Description:**

This is a triplex [three plunger rods] positive displacement, reciprocating, plunger pump, constructed of 316SS manifolds, 316SS valve assemblies, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings. These higher capacity plunger pumps are suitable for multi-gun and multi-nozzle, industrial high pressure systems and pumping special liquids such as DI water and salt water.

**Datasheet:** [2530-2530E-2531-2537 Data Sheet](#)

**Service Manual:** [25 Frame Plunger Service Manual](#)

**Accessories:**

**Oil**



[6107](#)

Crankcase Oil

**Regulator**

[7031.100](#)

SS Pressure Regulator

[7021.100](#)

SS Pressure Regulator

[7032.100](#)

SS Pressure Regulator

**Relief / Pop-Off Valve**



[9941](#)

Pop-Off Valve

[7034](#)

SS Pressure Relief Valve

**Pressure Gauge**



[6097](#)

Pressure Gauge

**Pulsation Dampener**



[6014](#)

Prrrrr-O-Lator-Rechg-NBR

**Captive Acceleration Tube**



[714500](#)

Captive Acceleration Tube


**Inlet Filter**



[7107.7](#)

Inlet Filter


#### Flexible Inlet Hose



[990847](#)

Flexible Inlet Hose

#### Flexible Discharge Hose



[990853](#)

Flexible Discharge Hose

#### LPS Monitors



[30290](#)

LPS Monitor



[30290.120AC](#)

LPS Monitor

#### Other



[34334](#)

Oil Drain Kit