

**Model: [2531.44101](#)**  
**25 FRAME PLUNGER PUMP - TEG**



**Specs**

<b>Max Flow:</b>	25 gpm
<b>Min Pressure:</b>	100 psi
<b>Max Pressure:</b>	1000 psi
<b>Inlet Port Size:</b>	1.25
<b>Discharge Port Size:</b>	0.75
<b>RPM:</b>	1025
<b>Drive Type(s):</b>	Belt
<b>Material:</b>	Stainless Steel (SS)

**Description:**

This is a positive displacement (PD), reciprocating, triplex (three plunger rods) plunger pump, constructed of 316 stainless steel manifolds, 316 stainless steel valve assemblies, solid ceramic plungers and FPM seals and o-rings. This pump has been designed to handle Triethylene Glycol (TEG) up to 240 degrees F (116 degrees C) the most common method for removing water from natural gas. Our electric/engine driven TEG pump product line has been field proven in the most rigorous dehydration conditions and will meet Hazardous Air Pollutants (HAP) compliance and lower regulatory costs. (see 2530.44101 for brass model)

**Datasheet: [2530.44101-2531.44101 Data Sheet](#)**

**Service Manual: [25 Frame Plunger Service Manual](#)**


**Accessories:**

**Regulator**

 [7022.100](#) SS Pressure Regulator

**Relief / Pop-Off Valve**

 [890713](#) SS Pop-Off Valve

 [890702](#) SS Regulating Relief Valve

**Pressure Gauge**

 [6073](#) Pressure Gauge

**Pulsation Dampener**

 [6013](#) Prrrr-O-Lator-Rechg-FPM

