



Model: [2537](#)
25 FRAME PLUNGER PUMP

Specs

Max Flow:	21 gpm
Min Pressure:	100 psi
Max Pressure:	1200 psi
Inlet Port Size:	1.25
Discharge Port Size:	0.75
RPM:	860
Drive Type(s):	Belt
Material:	Nickel Aluminum Bronze (NAB)

Description:

This is a triplex (three plunger rods) positive displacement, reciprocating, plunger pump, constructed of Nickel Aluminum Bronze manifolds, 316SS valve assemblies, solid ceramic plungers and standard NBR (Buna-N) seals and o-rings. These higher capacity plunger pumps are suitable for multi-gun and multi-nozzle, industrial high pressure systems and pumping special liquids such as salt water. [See also 316SS models]

Datasheet: [2530-2530E-2531-2537 Data Sheet](#)

Service Manual: [25 Frame Plunger Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator



[7022.100](#)

SS Pressure Regulator



[7032.100](#)

SS Pressure Regulator

Unloader



[7531](#)

Multiple Gun Pressure Unloader

Relief / Pop-Off Valve



[7533.100](#)

SS Pressure Relief Valve

Pressure Gauge



[6097](#)

Pressure Gauge

Pulsation Dampener



[6014](#)

Prrrrr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[714500](#)

Captive Acceleration Tube


Inlet Filter



[7107.7](#)

Inlet Filter


Flexible Inlet Hose



[990847](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990853](#)

Flexible Discharge Hose

LPS Monitors



[30290](#)

LPS Monitor



[30290.120AC](#)

LPS Monitor

Other



[34334](#)

Oil Drain Kit