



The Pumps with Nine Lives



Model: [270](#)
3 FRAME PLUNGER PUMP

Specs

Max Flow:	3.5 gpm
Min Pressure:	100 psi
Max Pressure:	1500 psi
Inlet Port Size:	0.5
Discharge Port Size:	0.37
RPM:	1420
Drive Type(s):	Belt
Material:	Brass (BB)

Description:

This is a triplex [three plunger rods] positive displacement, reciprocating, plunger pump, constructed of forged brass manifolds, 304 SS valve assemblies, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings. The 1725 RPM permits multiple drive options including direct drive, flexible coupling, clutch or belt drive. [see BD motor data sheet]

[Datasheet: 230-240-270 Data Sheet](#)

[Service Manual: 3 Frame Plunger Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator



[7002](#)

Pressure Regulator

Unloader



NO IMAGE AVAILABLE

[7500S](#)

Pressure Sensitive Regulating Unloader

Relief / Pop-Off Valve



[33962](#)

Pop-Off Valve

Pressure Gauge



[6088](#)

Pressure Gauge

Pulsation Dampener



[6029](#)

Prrrr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[711500](#)

Captive Acceleration Tube


Inlet Filter



[7104.4](#)

Inlet Filter


Flexible Inlet Hose



[990840](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990836](#)

Flexible Discharge Hose

Other



[34334](#)

Oil Drain Kit