



The Pumps with Nine Lives



**Model: [2831](#)
28 FRAME BLOCK-STYLE PLUNGER PUMP**

Specs

Max Flow:	25 gpm
Min Pressure:	100 psi
Max Pressure:	1000 psi
Inlet Port Size:	1.25
Discharge Port Size:	0.75
RPM:	1025
Drive Type(s):	Belt
Material:	Stainless Steel (SS)

Description:

This is a triplex [three plunger rods] positive displacement, reciprocating, plunger pump, constructed of a machined, 316SS block-style inlet and discharge manifolds, 316SS valve assemblies, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings. These pumps are suitable for harsh liquids like saltwater and leachate, special sanitizing chemicals and food products. See 2831K flushed model.

[Datasheet: 2831-2831K Data Sheet](#)

[Service Manual: 8-28 Frame Plunger Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator



[7022-100](#)

SS Pressure Regulator

Relief / Pop-Off Valve



[9941](#)

Pop-Off Valve



[7034](#)

SS Pressure Relief Valve

Pressure Gauge



[6097](#)

Pressure Gauge

Pulsation Dampener



[6015](#)

Prrrrr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[714500](#)

Captive Acceleration Tube

Inlet Filter



[7107.7](#)

Inlet Filter


Flexible Inlet Hose



[990847](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990853](#)

Flexible Discharge Hose

LPS Monitors



[30290](#)

LPS Monitor



[30290.120AC](#)

LPS Monitor

Other



[34334](#)

Oil Drain Kit