

**Model: [310](#)  
5 FRAME PLUNGER PUMP**



**Specs**

<b>Max Flow:</b>	4 gpm
<b>Min Pressure:</b>	100 psi
<b>Max Pressure:</b>	2200 psi
<b>Inlet Port Size:</b>	1/2"NPT
<b>Discharge Port Size:</b>	3/8"NPT
<b>RPM:</b>	950
<b>Drive Type(s):</b>	Belt
<b>Material:</b>	Brass (BB)

**Description:**

This is a triplex [three plunger rods] positive displacement, reciprocating, plunger pump, constructed of a forged brass manifold, 304SS valve assemblies, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings. [see also 316SS models]

**Datasheet:** [310-340-350-310B-340B-350B-310S-340S-350S Data Sheet](#)

**Service Manual:** [5-15 Frame Plunger Service Manual](#)

**Accessories:**

Oil



[6107](#)

Crankcase Oil

Regulator



[7003](#)

Pressure Regulator

Relief / Pop-Off Valve



[33962](#)

Pop-Off Valve

Pressure Gauge



[6088](#)

Pressure Gauge

Pulsation Dampener



[6029](#)

Prrrr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[711500](#)

Captive Acceleration Tube

## Inlet Filter



[7104.4](#)

Inlet Filter

## Flexible Inlet Hose



[990840](#)

Flexible Inlet Hose

## Flexible Discharge Hose



[990836](#)

Flexible Discharge Hose

## Other



[34334](#)

Oil Drain Kit