

Model: [310B](#)
5 FRAME PLUNGER PUMP



Specs

Max Flow:	4 gpm
Min Pressure:	100 psi
Max Pressure:	2200 psi
Inlet Port Size:	1/2"NPT
Discharge Port Size:	3/8"NPT
RPM:	950
Drive Type(s):	Belt
Material:	Brass (BB)

Description:

This is a triplex (three plunger rods) positive displacement, reciprocating, plunger pump, constructed of a special brass manifold, 304 stainless steel valve assemblies, solid ceramic plungers and standard NBR (Buna-N) seals and o-rings. (see also 316 stainless steel models)

[Datasheet: 310-340-350-310B-340B-350B-310S-340S-350S Data Sheet](#)

[Service Manual: 5-15 Frame Plunger Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator



[7003](#)

Pressure Regulator

Relief / Pop-Off Valve



[33962](#)

Pop-Off Valve

Pressure Gauge



[6088](#)

Pressure Gauge

Pulsation Dampener



[6029](#)

Pmmr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[711500](#)

Captive Acceleration Tube

Inlet Filter



[7104.4](#)

Inlet Filter

Flexible Inlet Hose



[990840](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990836](#)

Flexible Discharge Hose