



**Model: [310S](#)
5 PFR PLUNGER PUMP**

Specs

Max Flow:	4 gpm
Min Pressure:	100 psi
Max Pressure:	2200 psi
Inlet Port Size:	1/2"NPT
Discharge Port Size:	3/8"NPT
RPM:	950
Drive Type(s):	Belt
Material:	Brass (BB)

Description:

This is a triplex (three plunger rods) positive displacement, reciprocating, plunger pump, constructed with forged Brass manifolds, 304 SS valve assemblies, solid ceramic plungers and standard NBR [Bunea-N] seals and o-rings. The manifold features stainless steel sleeves in the seal and valve chambers for extended life in harsh water conditions. The 1725 RPM permits multiple drive options including direct drive, flexible coupling, clutch or belt drive. [see BD motor data sheet]

Datasheet: [310-340-350-310B-340B-350B-310S-340S-350S Data Sheet](#)

Service Manual: [5-15 Frame Plunger Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator



[7003](#)

Pressure Regulator

Relief / Pop-Off Valve



[33962](#)

Pop-Off Valve

Pressure Gauge



[6088](#)

Pressure Gauge

Pulsation Dampener



[6029](#)

Prrrrr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[711500](#)

Captive Acceleration Tube

Inlet Filter



[71044](#)

Inlet Filter

Flexible Inlet Hose



[990840](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990836](#)

Flexible Discharge Hose

Other



[34334](#)

Oil Drain Kit