



The Pumps with Nine Lives

Model: [311](#) 5 FRAME PLUNGER PUMP

Specs

Max Flow:	4 gpm
Min Pressure:	100 psi
Max Pressure:	2200 psi
Inlet Port Size:	1/2"NPT(F)
Discharge Port Size:	3/8"NPT(F)
RPM:	950
Drive Type(s):	Belt
Material:	Stainless Steel (SS)

Description:

This is a triplex [three plunger rods] positive displacement, reciprocating, plunger pump, constructed of a 316SS Manifolds, 316SS valve assemblies, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings.

Datasheet: [311-341-351-317-347-357 Data Sheet](#)

Service Manual: [5-15 Frame Plunger Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator



[7003.100](#)

SS Pressure Regulator

Unloader



[7501](#)

SS Pressure Sensitive Regulating Unloader

Relief / Pop-Off Valve



[9961](#)

SS Pop-Off Valve



[7501.100](#)

SS Pressure Relief Valve

Pressure Gauge



[6097](#)

Pressure Gauge

Pulsation Dampener



[6031](#)

Prrrrr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[711500](#)

Captive Acceleration Tube

Inlet Filter



[7104.4](#)

Inlet Filter

Flexible Inlet Hose



[990845](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990859](#)

Flexible Discharge Hose

Other



[34334](#)

Oil Drain Kit