



The Pumps with Nine Lives

## Model: [317](#) 5 FRAME PLUNGER PUMP



### Specs

Max Flow:	4 gpm
Min Pressure:	100 psi
Max Pressure:	1500 psi
Inlet Port Size:	0.5
Discharge Port Size:	0.37
RPM:	1190
Drive Type(s):	Belt
Material:	Nickel Aluminum Bronze (NAB)

### Description:

This is a triplex (three plunger rods) positive displacement, reciprocating, plunger pump, constructed of a Nickel Aluminum Bronze Mainfolds, 316 SS valve assemblies, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings.

Datasheet: [311-341-351-317-347-357 Data Sheet](#)

Service Manual: [5-15 Frame Plunger Service Manual](#)

### Accessories:

#### Oil



[6107](#)

Crankcase Oil

#### Regulator



[7003.100](#)

SS Pressure Regulator

#### Unloader

[7501](#)

SS Pressure Sensitive Regulating Unloader

#### Relief / Pop-Off Valve



[9961](#)

SS Pop-Off Valve

[7501.100](#)

SS Pressure Relief Valve

#### Pressure Gauge



[6097](#)

Pressure Gauge

#### Pulsation Dampener

[6029](#)

Prrrrr-O-Lator-Rechg-NBR



[6031](#)

Prrrrr-O-Lator-Rechg-NBR

### Captive Acceleration Tube



[711500](#)

Captive Acceleration Tube

### Inlet Filter



[7104.4](#)

Inlet Filter

### Flexible Inlet Hose



[990845](#)

Flexible Inlet Hose

### Flexible Discharge Hose



[990859](#)

Flexible Discharge Hose

### Other



[34334](#)

Oil Drain Kit