

Model: [323](#)
5 FRAME PISTON PUMP



Specs

| | |
|----------------------|------------|
| Max Flow: | 5 gpm |
| Min Pressure: | 100 psi |
| Max Pressure: | 1500 psi |
| Inlet Port Size: | 0.5 |
| Discharge Port Size: | 0.5 |
| RPM: | 1000 |
| Drive Type(s): | Belt |
| Material: | Brass (BB) |

Description:

This is a triplex [three piston rods] positive displacement, reciprocating, piston pump, constructed with brass manifolds, 304SS valve assemblies, chrome-plated 304SS cylinders and sleeves and standard NBR [Buna-N] seals and o-rings. Its low RPM is designed for belt drive. The Uniflow design features a mechanically actuated inlet valve providing a continuous forward fluid flow and strong suction. Features a side ported discharge manifold for convenient system plumbing.

Datasheet: [323-390 Data Sheet](#)

Service Manual: [Piston Pump Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator



[7002](#)

Pressure Regulator

Unloader



NO IMAGE AVAILABLE

[7500S](#)

Pressure Sensitive Regulating Unloader

Relief / Pop-Off Valve



[33962](#)

Pop-Off Valve

Pressure Gauge



[6088](#)

Pressure Gauge

Pulsation Dampener



[6029](#)

Prrrrr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[711500](#)

Captive Acceleration Tube


Inlet Filter



[7104.4](#)

Inlet Filter


Flexible Inlet Hose



[990840](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990836](#)

Flexible Discharge Hose

Other



[34334](#)

Oil Drain Kit