



The Pumps with Nine Lives

Model: [341](#) 5 FRAME PLUNGER PUMP



Specs

| | |
|----------------------|----------------------|
| Max Flow: | 4 gpm |
| Min Pressure: | 100 psi |
| Max Pressure: | 1800 psi |
| Inlet Port Size: | 0.5 |
| Discharge Port Size: | 0.37 |
| RPM: | 1725 |
| Drive Type(s): | Belt |
| Material: | Stainless Steel (SS) |

Description:

This is a triplex (three plunger rods) positive displacement, reciprocating, plunger pump, constructed of 316SS manifolds, 316SS valve assemblies, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings. The 1725 RPM permits a close coupled installation using a bell housing and flexible coupling or direct-drive motor-pump unit.

Datasheet: [311-341-351-317-347-357 Data Sheet](#)

Service Manual: [5-15 Frame Plunger Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator



[7002.100](#)

SS Pressure Regulator

Unloader

[7501](#)

SS Pressure Sensitive Regulating Unloader

Relief / Pop-Off Valve



[9961](#)

SS Pop-Off Valve

[7501.100](#)

SS Pressure Relief Valve

Pressure Gauge



[6097](#)

Pressure Gauge

Pulsation Dampener



[6031](#)

Prrrrr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[711500](#)

Captive Acceleration Tube

Inlet Filter



[7104.4](#)

Inlet Filter

Flexible Inlet Hose



[990845](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990859](#)

Flexible Discharge Hose

Other



[34334](#)

Oil Drain Kit