



The Pumps with Nine Lives

Model: [350S](#) 5 PFR PLUNGER PUMP



Specs

| | |
|----------------------|------------|
| Max Flow: | 5 gpm |
| Min Pressure: | 100 psi |
| Max Pressure: | 1500 psi |
| Inlet Port Size: | 0.5 |
| Discharge Port Size: | 0.37 |
| RPM: | 1725 |
| Drive Type(s): | Belt |
| Material: | Brass (BB) |

Description:

This is a triplex [three plunger rods] positive displacement, reciprocating, plunger pump, constructed with forged Brass manifolds, 304 SS valve assemblies, solid ceramic plungers and standard NBR [Bunea-N] seals and o-rings. The manifold features stainless steel sleeves in the seal and valve chambers for extended life in harsh water conditions. The 1725 RPM permits a close coupled installation using a bell housing and flexible coupling or direct-drive motor-pump unit.

Datasheet: [310-340-350-310B-340B-350B-310S-340S-350S Data Sheet](#)

Service Manual: [5-15 Frame Plunger Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator



[7002](#)

Pressure Regulator



[7082](#)

Pressure Regulator

Unloader



NO IMAGE AVAILABLE

[7500S](#)

Pressure Sensitive Regulating Unloader

Relief / Pop-Off Valve



[33962](#)

Pop-Off Valve

Pressure Gauge



[6088](#)

Pressure Gauge

Pulsation Dampener



[6029](#)

Prrrrr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[711500](#)

Captive Acceleration Tube


Inlet Filter



[71044](#)

Inlet Filter

Flexible Inlet Hose



[990840](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990836](#)

Flexible Discharge Hose

Other



[34334](#)

Oil Drain Kit