

**Model: [3520](#)  
35 FRAME PLUNGER PUMP**

**Specs**

<b>Max Flow:</b>	23 gpm
<b>Min Pressure:</b>	100 psi
<b>Max Pressure:</b>	2000 psi
<b>Inlet Port Size:</b>	1.5
<b>Discharge Port Size:</b>	1
<b>RPM:</b>	800
<b>Drive Type(s):</b>	Belt
<b>Material:</b>	Brass (BB)

**Description:**

This is a triplex [three plunger rods] positive displacement, reciprocating, plunger pump, constructed of forged brass manifolds, 304SS valve assemblies, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings. These higher capacity plunger pumps are suitable for multi-gun and multi-nozzle and industrial high pressure systems. [see also 316SS models]

**Datasheet:** [3520-3521-3527 Data Sheet](#)

**Service Manual:** [35 Frame Plunger Service Manual](#)

**Accessories:**

Oil



[6107](#)

Crankcase Oil

Regulator

[7022](#)

Pressure Regulator

Unloader

[7590](#)

Multiple Gun Pressure Unloader

Relief / Pop-Off Valve



[7595](#)

High Flow Relief Valve

Pressure Gauge



[6088](#)

Pressure Gauge

Pulsation Dampener



[6010](#)

Prrrr-O-Lator-Rechg-NBR

## Captive Acceleration Tube



[714500](#)

Captive Acceleration Tube

## Inlet Filter



[7108.8](#)

Inlet Filter

## Flexible Inlet Hose



[990844](#)

Flexible Inlet Hose

## Flexible Discharge Hose



[990833](#)

Flexible Discharge Hose