



**Model: [3521C](#)
35 FRAME FLUSHED PLUNGER PUMP**

Specs

Max Flow:	23 gpm
Min Pressure:	100 psi
Max Pressure:	2000 psi
Inlet Port Size:	1.5
Discharge Port Size:	1
RPM:	800
Drive Type(s):	Belt
Material:	Stainless Steel (SS)

Description:

This is a triplex (three plunger rods) positive displacement, reciprocating, plunger pump, constructed of 316SS manifold, 316SS valve assemblies, solid ceramic plungers and standard NBR (Buna-N) seals and o-rings. The C indicates the special flushed Inlet Manifold that permits an external flush liquid providing added cooling for hi-temp liquids and added lubrication for low-lubricity liquids such as DI water.

Datasheet: [3520-3521-3527 Data Sheet](#)

Service Manual: [35 Frame Plunger Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator



[7022.100](#)

SS Pressure Regulator

Relief / Pop-Off Valve



[9941](#)

Pop-Off Valve



[890711](#)

SS Pop-off Valve

Pressure Gauge



[6097](#)

Pressure Gauge

Pulsation Dampener



[6014](#)

Prrrr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[714500](#)

Captive Acceleration Tube


Inlet Filter



[7108.8](#)

Inlet Filter

Flexible Inlet Hose



[990850](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990854](#)

Flexible Discharge Hose

LPS Monitors



[30290](#)

LPS Monitor



[30290.120AC](#)

LPS Monitor