

**Model: [3527](#)  
35 FRAME PLUNGER PUMP**

**Specs**

<b>Max Flow:</b>	23 gpm
<b>Min Pressure:</b>	100 psi
<b>Max Pressure:</b>	2000 psi
<b>Inlet Port Size:</b>	1.5
<b>Discharge Port Size:</b>	1
<b>RPM:</b>	800
<b>Drive Type(s):</b>	Belt
<b>Material:</b>	Nickel Aluminum Bronze (NAB)

**Description:**

This is a triplex [three plunger rod] positive displacement, reciprocating, plunger pump, constructed of Nickel Aluminum Bronze manifolds, 316SS valve assemblies, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings. These higher capacity plunger pumps are suitable for multi-gun and multi-nozzle, industrial high pressure systems and pumping special liquids such as salt water. [See also 316SS models]

**Datasheet:** [3520-3521-3527 Data Sheet](#)

**Service Manual:** [35 Frame Plunger Service Manual](#)

**Accessories:**

**Oil**



[6107](#)

Crankcase Oil

**Regulator**

[7022.100](#)

SS Pressure Regulator

**Relief / Pop-Off Valve**



[890711](#)

SS Pop-off Valve

**Pressure Gauge**



[6097](#)

Pressure Gauge

**Pulsation Dampener**



[6014](#)

Prrrrr-O-Lator-Rechg-NBR

**Captive Acceleration Tube**



[714500](#)

Captive Acceleration Tube


**Inlet Filter**



[7108.8](#)

Inlet Filter


### Flexible Inlet Hose



[990850](#)

Flexible Inlet Hose

### Flexible Discharge Hose



[990854](#)

Flexible Discharge Hose

### LPS Monitors



[30290](#)

LPS Monitor



[30290.120AC](#)

LPS Monitor