



The Pumps with Nine Lives

Model: [3535](#) 35 FRAME PLUNGER PUMP



Specs

Max Flow:	36 gpm
Min Pressure:	100 psi
Max Pressure:	1200 psi
Inlet Port Size:	1.5
Discharge Port Size:	1
RPM:	800
Drive Type(s):	Belt
Material:	N/A

Description:

This is a triplex (three plunger rods) positive displacement, reciprocating, plunger pump, constructed of forged brass manifolds, 304SS valve assemblies, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings. These higher capacity plunger pumps are suitable for multi-gun and multi-nozzle and industrial high pressure systems. [see also 316SS models]

Datasheet: [3535-3531-3537 Data Sheet](#)

Service Manual: [35 Frame Plunger Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator



[7376](#)

SS Pressure Regulator

Unloader



[7590](#)

Multiple Gun Pressure Unloader

Relief / Pop-Off Valve



[7595](#)

High Flow Relief Valve

Pressure Gauge



[6088](#)

Pressure Gauge

Pulsation Dampener



[6010](#)

Prrrrr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[714500](#)

Captive Acceleration Tube


Inlet Filter



[7108.8](#)

Inlet Filter


Flexible Inlet Hose



[990844](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990833](#)

Flexible Discharge Hose

LPS Monitors



[30290](#)

LPS Monitor



[30290.120AC](#)

LPS Monitor