



**Model: [3537](#)
35 FRAME PLUNGER PUMP**

Specs

Max Flow:	36 gpm
Min Pressure:	100 psi
Max Pressure:	1200 psi
Inlet Port Size:	1.5
Discharge Port Size:	1
RPM:	800
Drive Type(s):	Belt
Material:	Nickel Aluminum Bronze (NAB)

Description:

This is a triplex (three plunger rods) positive displacement, reciprocating, plunger pump, constructed of Nickel Aluminum Bronze manifolds, 316SS valve assemblies, solid ceramic plungers and standard NBR (Buna-N) seals and o-rings. These higher capacity plunger pumps are suitable for multi-gun and multi-nozzle, industrial high pressure systems and pumping special liquids such as salt water. [See also 316SS models]

Datasheet: [3535-3531-3537 Data Sheet](#)

Service Manual: [35 Frame Plunger Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator



[7376](#)

SS Pressure Regulator

Relief / Pop-Off Valve



[890711](#)

SS Pop-off Valve

Pressure Gauge



[6097](#)

Pressure Gauge

Pulsation Dampener



[6015](#)

Prrrrr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[714500](#)

Captive Acceleration Tube

Inlet Filter



[7108.8](#)

Inlet Filter

Flexible Inlet Hose



[990850](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990854](#)

Flexible Discharge Hose

LPS Monitors



[30290](#)

LPS Monitor



[30290.120AC](#)

LPS Monitor