



Model: [3560](#)
35 FRAME PLUNGER PUMP

Specs

Max Flow:	20 gpm
Min Pressure:	100 psi
Max Pressure:	4000 psi
Inlet Port Size:	1.5
Discharge Port Size:	1
RPM:	1160
Drive Type(s):	Belt
Material:	Brass (BB)

Description:

This is a triplex [three plunger rods] positive displacement, reciprocating plunger pump constructed of a forged brass inlet manifold, 304SS stacked valve assemblies, solid ceramic plungers, NBR [Buna-N] seals and orings, STG with 4-screw valve plugs. This 35 Frame pump is designed for hydro blasting, tank cleaning, sewer cleaning and other high-pressure site clean up tasks. Alternate performance at 25 GPM @ 3000PSI.

Datasheet: [3560 Data Sheet](#)

Service Manual: [35 Frame Plunger Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator



[7024](#)

Pressure Regulator

Relief / Pop-Off Valve



[9940](#)

Pop-Off Valve



[7536.100](#)

SS Pressure Relief Valve

Pressure Gauge



[6089](#)

Pressure Gauge

Pulsation Dampener



[6011](#)

Prrrr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[714500](#)

Captive Acceleration Tube


Inlet Filter



[7108.8](#)

Inlet Filter

Flexible Inlet Hose



[990844](#)

Flexible Inlet Hose

LPS Monitors



[30290](#)

LPS Monitor



[30290.120AC](#)

LPS Monitor