



The Pumps with Nine Lives



**Model: [3811](#)
38 FRAME BLOCK-STYLE PLUNGER PUMP**

Specs

Max Flow:	14 gpm
Min Pressure:	100 psi
Max Pressure:	3000 psi
Inlet Port Size:	1.5
Discharge Port Size:	1
RPM:	800
Drive Type(s):	Belt
Material:	Stainless Steel (SS)

Description:

This is a triplex (three plunger rods) positive displacement, reciprocating, plunger pump, constructed of a machined, 316SS block-style inlet and discharge manifolds, 316SS valve assemblies, solid ceramic plungers and standard NBR (Buna-N) seals and o-rings. These pumps are suitable for harsh liquids like saltwater and leachate, special sanitizing chemicals and food products. See 3811K flushed model.

[Datasheet: 3801-3811K Data Sheet](#)

[Service Manual: 38 Frame Block-Style Plunger Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator



[7023.100](#)

SS Pressure Regulator

Unloader



[7533](#)

Multiple Gun Pressure Unloader

Relief / Pop-Off Valve



[9941](#)

Pop-Off Valve



[7036](#)

SS Pressure Relief Valve

Pressure Gauge



[6087](#)

Pressure Gauge

Pulsation Dampener



[701501](#)

Pulsation Dampener-Rebuild-NBR

Captive Acceleration Tube



[711500](#)

Captive Acceleration Tube


Inlet Filter



[7108.8](#)

Inlet Filter


Flexible Inlet Hose



[990850](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990854](#)

Flexible Discharge Hose

LPS Monitors



[30290](#)

LPS Monitor



[30290.120AC](#)

LPS Monitor