



The Pumps with Nine Lives



**Model: [3811K](#)  
38 FRAME BLOCK-STYLE PLUNGER PUMP**

**Specs**

<b>Max Flow:</b>	14 gpm
<b>Min Pressure:</b>	100 psi
<b>Max Pressure:</b>	3000 psi
<b>Inlet Port Size:</b>	1.5
<b>Discharge Port Size:</b>	1
<b>RPM:</b>	800
<b>Drive Type(s):</b>	Belt
<b>Material:</b>	Stainless Steel (SS)

**Description:**

This is a triplex [three plunger rods] positive displacement, reciprocating, plunger pump, constructed of a machined, 316SS block-style inlet and discharge manifolds, 316SS valve assemblies, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings. These pumps are suitable for harsh liquids like saltwater and leachate, special sanitizing chemicals and food products. The K indicates the special flushed Inlet Manifold that permits an external flush liquid providing added cooling for hi-temp liquids and added lubrication for low-lubricity liquids such as DI water. Used with the 990663 Flushing Assembly, it offers containment of effluent emissions for environmental safety.

[Datasheet: 3801-3811K Data Sheet](#)

[Service Manual: 38 Frame Block-Style Plunger Service Manual](#)

**Accessories:**

**Oil**



[6107](#)

Crankcase Oil


**Regulator**



[7023.100](#)

SS Pressure Regulator

**Unloader**



[7533](#)

Multiple Gun Pressure Unloader

**Relief / Pop-Off Valve**



[9941](#)

Pop-Off Valve



[7036](#)

SS Pressure Relief Valve

**Pressure Gauge**



[6087](#)

Pressure Gauge

**Pulsation Dampener**



[701501](#)

Pulsation Dampener-Rebuild-NBR

**Captive Acceleration Tube**



[711500](#)

Captive Acceleration Tube

**Inlet Filter**



[7106.6](#)

Inlet Filter


### Flexible Inlet Hose



[990850](#)

Flexible Inlet Hose

### Flexible Discharge Hose



[990854](#)

Flexible Discharge Hose

### LPS Monitors



[30290](#)

LPS Monitor



[30290.120AC](#)

LPS Monitor