



The Pumps with Nine Lives



Model: [3831](#) 38 FRAME BLOCK-STYLE PLUNGER PUMP

Specs

Max Flow:	36 gpm
Min Pressure:	100 psi
Max Pressure:	1200 psi
Inlet Port Size:	1.5
Discharge Port Size:	1
RPM:	800
Drive Type(s):	Belt
Material:	Stainless Steel (SS)

Description:

This is a triplex [three plunger rods] positive displacement, reciprocating, plunger pump, constructed of a machined, 316SS block-style inlet and discharge manifolds, 316SS valve assemblies, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings. These pumps are suitable for harsh liquids like saltwater and leachate, special sanitizing chemicals and food products. See 3831K flushed model.

Datasheet: [3821-3831K Data Sheet](#)

Service Manual: [38 Frame Block-Style Plunger Service Manual](#)

Accessories:

Regulator

 [7376](#) SS Pressure Regulator



[7363](#) SS Pressure Regulator

Pressure Gauge



[6097](#) Pressure Gauge

Pulsation Dampener

 [6013](#) Prrrr-O-Lator-Rechg-FPM



[6015](#) Prrrr-O-Lator-Rechg-NBR

 [701503](#) Pulsation Dampener-Rebuild-NBR

Captive Acceleration Tube



[714506](#) Adapter-C.A.T.



[714500](#) Captive Acceleration Tube

Inlet Filter



[7108](#)


Inlet Filter



[7108.8](#)

Inlet Filter

Flexible Inlet Hose



[990847](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990854](#)

Flexible Discharge Hose