

**Model: [390](#)  
5 FRAME PISTON PUMP**



**Specs**

<b>Max Flow:</b>	12 gpm
<b>Min Pressure:</b>	100 psi
<b>Max Pressure:</b>	600 psi
<b>Inlet Port Size:</b>	1
<b>Discharge Port Size:</b>	0.5
<b>RPM:</b>	1200
<b>Drive Type(s):</b>	Belt
<b>Material:</b>	Brass (BB)

**Description:**

This is a triplex [three piston rods] positive displacement, reciprocating, piston pump, constructed with brass manifolds, 304SS valve assemblies, chrome-plated 304SS cylinders and sleeves and standard NBR [Buna-N] seals and o-rings. Its low RPM is designed for belt drive. The Uniflow design features a mechanically actuated inlet valve providing a continuous forward fluid flow and strong suction. Features side ported inlet and discharge manifold for convenient system plumbing.

**Datasheet:** [323-390 Data Sheet](#)

**Service Manual:** [Piston Pump Service Manual](#)

**Accessories:**

**Oil**



[6107](#) Crankcase Oil

**Regulator**



[7021](#) Pressure Regulator

**Pressure Gauge**



[6086](#) Pressure Gauge

**Pulsation Dampener**



[6029](#) Pmmr-O-Lator-Rechg-NBR

**Captive Acceleration Tube**



[711500](#) Captive Acceleration Tube

**Inlet Filter**




[7106](#) Inlet Filter



[7106.6](#)

Inlet Filter


### Flexible Inlet Hose



[990842](#)

Flexible Inlet Hose

### Flexible Discharge Hose



[990836](#)

Flexible Discharge Hose

### Other



[34334](#)

Oil Drain Kit