



The Pumps with Nine Lives

Model: [3CP1130.3000](#)
3CP PLUNGER PUMP - HIGH TEMP.



Specs

| | |
|-----------------------------|------------|
| Max Flow: | 2.4 gpm |
| Min Pressure: | 100 psi |
| Max Pressure: | 2200 psi |
| Inlet Port Size: | 0.5 |
| Discharge Port Size: | 0.37 |
| RPM: | 1725 |
| Drive Type(s): | Belt |
| Material: | Brass (BB) |

Description:

This is a triplex (three plunger rods) positive displacement, reciprocating, plunger pump, constructed of a forged brass manifold, 304 stainless steel valve assemblies, solid ceramic plungers and standard NBR (Buna-N) o-rings and low pressure seals. High pressure seals are a special blend PTFE for high temperature applications.

Datasheet: [3CP1120-1130-1140-1120G Data Sheet](#)

Service Manual: [CP Plunger Service Manual](#)

Accessories:

Pulsation Dampener



[6030](#)

Prrrrr-O-Lator-Rechg-FPM

Pressure Gauge



[6097](#)

Pressure Gauge

Relief / Pop-Off Valve



[33961S](#)

Pop-Off Valve - High Temp.

Regulator



[7003](#)

Pressure Regulator