



The Pumps with Nine Lives

**Model: [3CP1221](#)
3CP PLUNGER PUMP**



Specs

Max Flow:	4.2 gpm
Min Pressure:	100 psi
Max Pressure:	2000 psi
Inlet Port Size:	0.5
Discharge Port Size:	0.37
RPM:	1725
Drive Type(s):	Belt
Material:	Stainless Steel (SS)

Description:

This is a triplex [three plunger rods] positive displacement, reciprocating, plunger pump, constructed of a 316 SS Mainfolds, 316 SS valve assemblies, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings.

Datasheet: [3CP1221-1231-1241 Data Sheet](#)

Service Manual: [CP Stainless Steel Plunger Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator



[7002.100](#)

SS Pressure Regulator



[7003.100](#)

SS Pressure Regulator

Unloader



[7501](#)

SS Pressure Sensitive Regulating Unloader

Relief / Pop-Off Valve



[9961](#)

SS Pop-Off Valve

Pressure Gauge



[6097](#)

Pressure Gauge

Pulsation Dampener



[6029](#)

Prrrrr-O-Lator-Rechg-NBR



[6031](#)

Prrrrr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[711500](#)

Captive Acceleration Tube

Inlet Filter



[7104.4](#)

Inlet Filter

Flexible Inlet Hose



[990845](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990859](#)

Flexible Discharge Hose

Other



[34334](#)

Oil Drain Kit