

**Model: [3CP1231.44101](#)
3CP SS PLUNGER PUMP - TEG**



Specs

Max Flow:	2.3 gpm
Min Pressure:	100 psi
Max Pressure:	2000 psi
Inlet Port Size:	0.5
Discharge Port Size:	0.37
RPM:	1725
Drive Type(s):	Belt
Material:	Stainless Steel (SS)

Description:

This is a positive displacement (PD), reciprocating, triplex (three plunger rods) plunger pump, constructed of 316 stainless steel manifolds, 316 stainless steel valve assemblies, solid ceramic plungers and FPM seals and o-rings. This pump has been designed to handle Triethylene Glycol (TEG) up to 240 degrees F (116 degrees C) the most common method for removing water from natural gas. Our electric/engine driven TEG pump product line has been field proven in the most rigorous dehydration conditions and will meet Hazardous Air Pollutants (HAP) compliance and lower regulatory cost. (see 3CP1130.44101 for brass model)

Datasheet: [3CP1221.44101-3CP1231.44101-3CP1241.44101 Data Sheet](#)

Service Manual: [CP Stainless Steel Plunger Service Manual](#)

Accessories:

Regulator



[7003.100](#)

SS Pressure Regulator

Unloader



[7501](#)

SS Pressure Sensitive Regulating Unloader

Relief / Pop-Off Valve



[7501.100](#)

SS Pressure Relief Valve

Pressure Gauge



[6073](#)

Pressure Gauge

Pulsation Dampener



[6030](#)

Pmmr-O-Lator-Rechg-FPM