



**Model: [45](#)**  
**5 FRAME PLUNGER PUMP**

**Specs**

Max Flow:	4.5 gpm
Min Pressure:	100 psi
Max Pressure:	3500 psi
Inlet Port Size:	0.5
Discharge Port Size:	0.37
RPM:	1645
Drive Type(s):	Belt
Material:	Brass (BB)

**Description:**

This is a triplex [three plunger rods] positive displacement, reciprocating, plunger pump, constructed of a forged brass manifold, 304SS valve assemblies, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings.

**Datasheet:** [45-45G1 Data Sheet](#)

**Service Manual:** [5-15 Frame Plunger Service Manual](#)

**Accessories:**

**Oil**



[6107](#) Crankcase Oil

**Regulator**



[7014](#) Pressure Regulator

**Relief / Pop-Off Valve**



[33962](#) Pop-Off Valve

**Pressure Gauge**



[6089](#) Pressure Gauge

**Pulsation Dampener**



[6011](#) Prrrr-O-Lator-Rechg-NBR

**Captive Acceleration Tube**



[711500](#)

Captive Acceleration Tube

### Inlet Filter



[7104.4](#)

Inlet Filter

### Flexible Inlet Hose



[990840](#)

Flexible Inlet Hose

### Flexible Discharge Hose



[990857](#)

Flexible Discharge Hose

### Other



[34334](#)

Oil Drain Kit