



The Pumps with Nine Lives

**Model: [5CP2150B](#)  
5CP PLUNGER PUMP**

**Specs**

<b>Max Flow:</b>	5 gpm
<b>Min Pressure:</b>	100 psi
<b>Max Pressure:</b>	2000 psi
<b>Inlet Port Size:</b>	0.5
<b>Discharge Port Size:</b>	0.37
<b>RPM:</b>	1725
<b>Drive Type(s):</b>	Belt
<b>Material:</b>	Brass (BB)

**Description:**

This is a triplex (three plunger rods) positive displacement, reciprocating, plunger pump, constructed of a special brass manifold, 304 stainless steel valve assemblies, solid ceramic plungers and standard NBR (Buna-N) seals and o-rings. The 1725 RPM permits multiple drive options including direct drive, flexible coupling, clutch or belt drive.

**Datasheet:** [5CP2120W-2140WCS-2150W Data Sheet](#)

**Service Manual:** [CP Plunger Service Manual](#)

**Accessories:**

**Oil**



[6107](#)

Crankcase Oil

**Regulator**



[7002](#)

Pressure Regulator

**Unloader**



[7850](#)

Modular Pressure Unloader

**Relief / Pop-Off Valve**



[33962](#)

Pop-Off Valve

**Pressure Gauge**



[6088](#)

Pressure Gauge

**Pulsation Dampener**



[6029](#)

Prrrrr-O-Lator-Rechg-NBR

**Captive Acceleration Tube**



[711500](#)

Captive Acceleration Tube


## Inlet Filter



[7104.4](#)

Inlet Filter


## Flexible Inlet Hose



[990840](#)

Flexible Inlet Hose

## Flexible Discharge Hose



[990836](#)

Flexible Discharge Hose

## Other



[34334](#)

Oil Drain Kit