



The Pumps with Nine Lives

**Model: [5CP2150W](#)
5CP PLUNGER PUMP**

Specs

Max Flow:	5 gpm
Min Pressure:	100 psi
Max Pressure:	2000 psi
Inlet Port Size:	0.5
Discharge Port Size:	0.37
RPM:	1725
Drive Type(s):	Belt
Material:	N/A

Description:

This is a triplex (three plunger rods) positive displacement, reciprocating, plunger pump, constructed of a special W770 manifold, 304SS valve assemblies, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings. The 1725 RPM permits a close coupled installation using a bell housing and flexible coupling or direct-drive motor-pump unit.

Datasheet: [5CP2120W-2140WCS-2150W Data Sheet](#)

Service Manual: [CP Plunger Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator



[7002](#)

Pressure Regulator

Unloader



[7850](#)

Modular Pressure Unloader

Relief / Pop-Off Valve



[33962](#)

Pop-Off Valve

Pressure Gauge



[6088](#)

Pressure Gauge

Pulsation Dampener



[6029](#)

Prrrrr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[711500](#)

Captive Acceleration Tube


Inlet Filter



[7104.4](#)

Inlet Filter


Flexible Inlet Hose



[990840](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990836](#)

Flexible Discharge Hose

Other



[34334](#)

Oil Drain Kit