

**Model: [5CP6120CSSG1](#)
5CP PUMP WITH GEARBOX**



Specs

Max Flow:	6.7 gpm
Min Pressure:	100 psi
Max Pressure:	1600 psi
Inlet Port Size:	0.5
Discharge Port Size:	0.37
RPM:	1570
Drive Type(s):	Gearbox
Material:	Brass (BB)

Description:

This is a triplex (three plunger rods) positive displacement, reciprocating, plunger pump, constructed of a chrome-plated, forged brass manifold, 304 stainless steel valve assemblies, solid ceramic plungers and standard NBR (Buna-N) seals and o-rings. Includes side bubble gauge. (see also 316 stainless steel models)

Datasheet: [5CP6120-6190-6120CSSG1-6190G1 Data Sheet](#)

Service Manual: [CP Plunger Service Manual](#)

Accessories:

- Oil
 -  [6107](#) Crankcase Oil
- Regulator
 -  [7012](#) Pressure Regulator
- Relief / Pop-Off Valve
 -  [9940](#) Pop-Off Valve
- Pressure Gauge
 -  [6088](#) Pressure Gauge
- Pulsation Dampener
 -  [6029](#) Pmmr-O-Lator-Rechg-NBR
- Captive Acceleration Tube
 -  [711500](#) Captive Acceleration Tube
- Inlet Filter



[7105.5](#)

Inlet Filter

Flexible Inlet Hose



[990840](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990836](#)

Flexible Discharge Hose

Other



[34334](#)

Oil Drain Kit