



The Pumps with Nine Lives

**Model: [5CP6190G1](#)  
5CP PUMP WITH GEARBOOX**



**Specs**

|                      |            |
|----------------------|------------|
| Max Flow:            | 8.7 gpm    |
| Min Pressure:        | 100 psi    |
| Max Pressure:        | 1200 psi   |
| Inlet Port Size:     | 0.5        |
| Discharge Port Size: | 0.37       |
| RPM:                 | 1570       |
| Drive Type(s):       | Gearbox    |
| Material:            | Brass (BB) |

**Description:**

This is a triplex (three plunger rods) positive displacement, reciprocating, direct-drive, plunger pump, constructed of a chrome-plated forged brass manifold, 304 stainless steel valve assemblies, solid ceramic plungers and standard NBR (Buna-N) seals and o-rings.

**Datasheet:** [5CP6120-6190-6120CSSG1-6190G1 Data Sheet](#)

**Service Manual:** [CP Plunger Service Manual](#)

**Accessories:**

**Oil**



[6107](#)

Crankcase Oil

**Regulator**



[7012](#)

Pressure Regulator

**Relief / Pop-Off Valve**



[9940](#)

Pop-Off Valve

**Pressure Gauge**



[6088](#)

Pressure Gauge

**Pulsation Dampener**



[6029](#)

Pmmr-O-Lator-Rechg-NBR

**Captive Acceleration Tube**



[711500](#)

Captive Acceleration Tube

**Inlet Filter**



[7104](#)


Inlet Filter



[7104.4](#)

Inlet Filter

### Flexible Inlet Hose



[990840](#)

Flexible Inlet Hose

### Flexible Discharge Hose



[990836](#)

Flexible Discharge Hose

### Other



[34334](#)

Oil Drain Kit