



The Pumps with Nine Lives

Model: [6010](#)

Prrrrr-O-Lator-Rechg-NBR



Specs

Max Flow:	40 gpm
-----------	--------

Min Pressure:	200 psi
---------------	---------

Max Pressure:	3000 psi
---------------	----------

Inlet Port Size:	0.5
------------------	-----

Discharge Port Size:	0.5
----------------------	-----

Type of Accessory:	Pulsation Dampener
--------------------	--------------------

Material:	Steel (STL)
-----------	-------------

Description:

This valve is designed to reduce pressure fluctuations or pulsation common in all positive displacement pump systems. It must be nitrogen pre-charged prior to installation on the discharge side of the pump. It will prolong the life of the pump and system components by reducing pulsation to + or- 3%.

Accessory to be used with these Pumps:

[2530](#) 25 FRAME PLUNGER PUMP



[3535](#) FRAME PLUNGER PUMP



[3520C35](#) FRAME FLUSHED PLUNGER PUMP



[2510](#) 25 FRAME PLUNGER PUMP

[2520](#) 25 FRAME PISTON PUMP



[1530](#) 15 FRAME PLUNGER PUMP

[3520](#) 35 FRAME PLUNGER PUMP



[6040](#)60 FRAME PISTON PUMP

[1520](#)25 FRAME PISTON PUMP



[1525](#)25 FRAME PISTON PUMP with PULSE PUMP MANIFOLD

[2530E](#)25 FRAME PLUNGER PUMP



[6044](#) OBSOLETE 60 FRAME PISTON PUMP



[1015](#)10 FRAME PISTON PUMP with PULSE PUMP MANIFOLD

[1540E](#)15 FRAME PLUNGER PUMP

[3560ALT](#)35 FRAME PLUNGER PUMP

[2530ALT](#)25 FRAME PLUNGER PUMP



[351C35](#) FRAME PLUNGER PUMP