

**Model: [6011](#)  
Prrrrr-O-Lator-Rechg-NBR**

**Specs**

Max Flow:	25 gpm
Min Pressure:	600 psi
Max Pressure:	7200 psi
Inlet Port Size:	0.5
Discharge Port Size:	0.5
Type of Accessory:	Pulsation Dampener
Material:	Steel (STL)

**Description:**

This valve is designed to reduce pressure fluctuations or pulsation common in all positive displacement pump systems. It must be nitrogen pre-charged prior to installation on the discharge side of the pump. It will prolong the life of the pump and system components by reducing pulsation to + or -3%.

**Accessory to be used with these Pumps:**

- [5CP3120CSS5](#)5CP PLUNGER PUMP
- [3501C35](#)35 FRAME PLUNGER PUMP
- [4SF40GS14](#)SF DIRECT DRIVE PLUNGER PUMPS
- [157015](#)15 FRAME PLUNGER PUMP
- [5CP5140CSSG15](#)CP PUMP WITH GEARBOX
- [4SF32ELS4](#)SF DIRECT DRIVE PLUNGER PUMPS
- [455](#)5 FRAME PLUNGER PUMP
- [45G15](#)FR PUMP WITH GEARBOX
- [567](#)7 FRAME PLUNGER PUMP
- [5CP3120CSSG15](#)CP PUMP WITH GEARBOX
- [60G17](#)FR PUMP WITH GEARBOX
- [4SF40ELS4](#)SF DIRECT DRIVE PLUNGER PUMPS
- [5CP3120ALT5](#)CP PLUNGER PUMP
- [5CP3105CSS5](#)CP PLUNGER PUMP
- [4SF35GS14](#)SF DIRECT DRIVE PLUNGER PUMPS
- [59G1](#)OBSOLETE 7FR PUMP WITH GEARBOX
- [59G118](#)OBSOLETE 7FR PUMP WITH GEARBOX
- [356035](#)35 FRAME PLUNGER PUMP
- [60G118](#)OBSOLETE 7FR PUMP WITH GEARBOX
- [70G1](#)OBSOLETE 7FR PUMP WITH GEARBOX
- [70G118](#)OBSOLETE 7FR PUMP WITH GEARBOX
- [6024](#)OBSOLETE 60 FRAME PISTON PUMP
- [5CP3120G15](#)CP PUMP WITH GEARBOX
- [156015](#)15 FRAME PLUNGER PUMP
- [59](#)OBSOLETE 7 FRAME PLUNGER PUMP
- [607](#)7 FRAME PLUNGER PUMP
- [3511C35](#)35 FRAME PLUNGER PUMP
- [66DX30G11](#)66DX DIRECT DRIVE PLUNGER PUMPS
- [577](#)7 FRAME PLUNGER PUMP
- [70](#)OBSOLETE 7 FRAME PLUNGER PUMP
- [66DX35G11](#)66DX DIRECT DRIVE PLUNGER PUMPS
- [66DX40G11](#)66DX DIRECT DRIVE PLUNGER PUMPS
- [5CP31205](#)CP PLUNGER PUMP