



**Model: [6028](#)
Prrrrr-O-Lator-Sealed-NBR**

Specs

Max Flow:	15 gpm
Min Pressure:	600 psi
Max Pressure:	1000 psi
Inlet Port Size:	0.5
Discharge Port Size:	0.05
Type of Accessory:	Pulsation Dampener
Material:	Steel (STL)

Description:

This valve is designed to reduce pressure fluctuations or pulsation common in all positive displacement pump systems. This nitrogen pre-charged at the factory ready to be installed on the discharge side of the pump. It will prolong the life of the pump and system components by reducing pulsation to + or- 3%. This valve is sealed and comes precharged to 450 PSI for system operating pressures of 600-3000 PSI.

Accessory to be used with these Pumps:



[2SF25ELS2SF](#) DIRECT DRIVE PLUNGER PUMPS



[65015](#) FRAME PLUNGER PUMP

[152025](#) FRAME PISTON PUMP



[1525](#)25 FRAME PISTON PUMP with PULSE PUMP MANIFOLD

[5CP5150G15](#)CP PUMP WITH GEARBOX

[5CP5150G118](#)OBSOLETE 5CP PUMP WITH GEARBOX



[34G15FR](#) PUMP WITH GEARBOX



[35G1](#) OBSOLETE 5FR PUMP WITH GEARBOX



[35G1185FR](#) PUMP WITH GEARBOX



[51G1](#) OBSOLETE 7FR PUMP WITH GEARBOX



[58G1](#) OBSOLETE 7FR PUMP WITH GEARBOX



[58G118](#) OBSOLETE 7FR PUMP WITH GEARBOX

[56G118](#) OBSOLETE 7FR PUMP WITH GEARBOX



[51G118](#) OBSOLETE 7FR PUMP WITH GEARBOX



[1015](#)10 FRAME PISTON PUMP with PULSE PUMP MANIFOLD



[35](#)OBSOLETE 5 FRAME PLUNGER PUMP



[305](#) FRAME PLUNGER PUMP



[53](#) OBSOLETE 7 FRAME PLUNGER PUMP



[55](#) OBSOLETE 7 FRAME PLUNGER PUMP



[51](#)OBSOLETE 7 FRAME PLUNGER PUMP



[58](#)OBSOLETE 7 FRAME PLUNGER PUMP

[45G1185FR](#) PUMP WITH GEARBOX



[31](#)OBSOLETE 5 FRAME PLUNGER PUMP



[34](#)OBSOLETE 5 FRAME PLUNGER PUMP



[310W](#) OBSOLETE 5 frame plunger pump



[340W](#) OBSOLETE 5 frame plunger pump



[350W](#) OBSOLETE 5 frame plunger pump



[2403](#) FRAME PLUNGER PUMP

[1010](#)10 FRAME PISTON PUMP
