



**Model: [623](#)  
10 FRAME PISTON PUMP**

**Specs**

<b>Max Flow:</b>	6 gpm
<b>Min Pressure:</b>	100 psi
<b>Max Pressure:</b>	1200 psi
<b>Inlet Port Size:</b>	1
<b>Discharge Port Size:</b>	0.75
<b>RPM:</b>	850
<b>Drive Type(s):</b>	Belt
<b>Material:</b>	Brass (BB)

**Description:**

This is a triplex [three piston rods] positive displacement, reciprocating, piston pump, constructed with brass manifolds, 304SS valve assemblies, chrome-plated 304SS cylinders and sleeves and standard NBR [Buna-N] seals and o-rings. Its low RPM is designed for belt drive. The Uniflow design features a mechanically actuated inlet valve providing a continuous forward fluid flow and strong suction.

**Datasheet:** [623-820-1010 Data Sheet](#)

**Service Manual:** [Piston Pump Service Manual](#)

**Accessories:**

**Oil**



[6107](#)

Crankcase Oil

**Regulator**



[7012](#)

Pressure Regulator

**Unloader**



NO IMAGE AVAILABLE

[7500S](#)

Pressure Sensitive Regulating Unloader

**Relief / Pop-Off Valve**



[33962](#)

Pop-Off Valve

**Pressure Gauge**



[6088](#)

Pressure Gauge

**Pulsation Dampener**



[6029](#)

Prrrrr-O-Lator-Rechg-NBR

**Captive Acceleration Tube**



[711500](#)

Captive Acceleration Tube

## Inlet Filter



[7105.5](#)

Inlet Filter

## Flexible Inlet Hose



[990840](#)

Flexible Inlet Hose

## Flexible Discharge Hose



[990832](#)

Flexible Discharge Hose

## Other



[34334](#)

Oil Drain Kit