

**Model: [661C](#)  
15 FRAME PLUNGER PUMP**



**Specs**

Max Flow:	10 gpm
Min Pressure:	100 psi
Max Pressure:	3000 psi
Inlet Port Size:	3/4"NPT(F)
Discharge Port Size:	1/2"NPT(F)
RPM:	1429
Drive Type(s):	Belt
Material:	Duplex (SSD)

**Description:**

This is a triplex [three plunger rods] positive displacement, reciprocating, plunger pump, constructed of 316SS manifold, 316SS valve assemblies, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings. The C indicates the special flushed Inlet Manifold that permits an external flush liquid providing added cooling for hi-temp liquids and added lubrication for low-lubricity liquids such as DI water.

**Datasheet:** [660-661D-661C Data Sheet](#)

**Service Manual:** [5-15 Frame Plunger Service Manual](#)

**Accessories:**

**Oil**



[6107](#) Crankcase Oil

**Regulator**

[7013.100](#) SS Pressure Regulator

**Unloader**

[7533](#) Multiple Gun Pressure Unloader

**Relief / Pop-Off Valve**



[9941](#) Pop-Off Valve

[7036](#) SS Pressure Relief Valve

**Pressure Gauge**




[6087](#) Pressure Gauge

**Pulsation Dampener**



[701501](#) Pulsation Dampener-Rebuild-NBR

**Captive Acceleration Tube**



[711500](#) Captive Acceleration Tube


**Inlet Filter**



[7105.5](#)

Inlet Filter


#### Flexible Inlet Hose



[990849](#)

Flexible Inlet Hose

#### Flexible Discharge Hose



[990852](#)

Flexible Discharge Hose

#### LPS Monitors



[30664](#)

LPS Monitor



[30664.120AC](#)

LPS Monitor

#### Other



[34334](#)

Oil Drain Kit