

**Model: [6775](#)**  
**60 FRAME PLUNGER PUMP**

**Specs**

<b>Max Flow:</b>	75 gpm
<b>Min Pressure:</b>	100 psi
<b>Max Pressure:</b>	1200 psi
<b>Inlet Port Size:</b>	2
<b>Discharge Port Size:</b>	1.25
<b>RPM:</b>	650
<b>Drive Type(s):</b>	Belt
<b>Material:</b>	Brass (BB)

**Description:**

This is a triplex [three plunger rods] positive displacement, reciprocating, plunger pump, constructed of forged brass manifolds, 316SS guided valve design, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings. These higher capacity plunger pumps are suitable for multi-gun and multi-nozzle and industrial high pressure systems.

**Datasheet:** [6775-6771-6777 Data Sheet](#)

**Service Manual:** [60 Frame Plunger Service Manual](#)

**Accessories:**

**Oil**



[6107](#)

Crankcase Oil

**Regulator**



[7376](#)

SS Pressure Regulator

**Relief / Pop-Off Valve**



[890700](#)

SS Regulating Relief Valve

**Pressure Gauge**



[6088](#)

Pressure Gauge

**Pulsation Dampener**



[701503](#)

Pulsation Dampener-Rebuild-NBR

**Captive Acceleration Tube**



[717500](#)

Captive Acceleration Tube

## Inlet Filter



[7109](#)

Inlet Filter

## Flexible Inlet Hose



[990851](#)

Flexible Inlet Hose

## Flexible Discharge Hose



[990839](#)

Flexible Discharge Hose