



The Pumps with Nine Lives

**Model: [6801K](#)
68 FRAME BLOCK-STYLE PLUNGER PUMP**



Specs

Max Flow:	15 gpm
Min Pressure:	1000 psi
Max Pressure:	7000 psi
Inlet Port Size:	1.5
Discharge Port Size:	1
RPM:	600
Drive Type(s):	Belt
Material:	Duplex (SSD)

Description:

This is a triplex [three plunger rods] positive displacement, reciprocating, plunger pump, constructed of a machined, 316SS block-style inlet and Duplex SS discharge manifolds, 316SS valve assemblies, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings. These pumps are suitable for harsh liquids like saltwater and leachate, special sanitizing chemicals and food products. The K indicates the special flushed Inlet Manifold that permits an external flush liquid providing added cooling for hi-temp liquids and added lubrication for low-lubricity liquids such as DI water. Used with the 990663 Flushing Assembly, it offers containment of effluent emissions for environmental safety.

Datasheet: [6801-6811K Data Sheet](#)

Service Manual: [68 Frame Block-Style Plunger Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Relief / Pop-Off Valve



[890715](#)

SS Pop-off Valve



[890718](#)

SS Regulating Relief Valve

Pressure Gauge



[6081](#)

Pressure Gauge

Pulsation Dampener



[701520](#)

Pulsation Dampener - Rebuild NBR

Captive Acceleration Tube



[711500](#)

Captive Acceleration Tube

Inlet Filter



[7106.6](#)

Inlet Filter

Flexible Inlet Hose



[990850](#)

Flexible Inlet Hose