



Model: [6821K](#)
68 FRAME BLOCK-STYLE PLUNGER PUMP



Specs

Max Flow:	25 gpm
Min Pressure:	100 psi
Max Pressure:	3000 psi
Inlet Port Size:	1.5
Discharge Port Size:	1
RPM:	615
Drive Type(s):	Belt
Material:	Stainless Steel (SS)

Description:

This is a triplex (three plunger rods) positive displacement, reciprocating, plunger pump, constructed of a machined, 316SS block-style inlet and discharge manifolds, 316SS valve assemblies, solid ceramic plungers and standard NBR (Buna-N) seals and o-rings. These pumps are suitable for harsh liquids like saltwater and leachate, special sanitizing chemicals and food products. The K indicates the special flushed Inlet Manifold that permits an external flush liquid providing added cooling for hi-temp liquids and added lubrication for low-lubricity liquids such as DI water. Used with the 990663 Flushing Assembly, it offers containment of effluent emissions for environmental safety.

Datasheet: [6821-6821K Data Sheet](#)

Service Manual: [68 Frame Block-Style Plunger Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator

[7033.100](#)

SS Pressure Regulator

[7023.100](#)

SS Pressure Regulator

Unloader

[7533](#)

Multiple Gun Pressure Unloader

Relief / Pop-Off Valve



[9941](#)

Pop-Off Valve



[890711](#)

SS Pop-off Valve

Pressure Gauge



[6087](#)

Pressure Gauge

Pulsation Dampener



[701502](#)

Pulsation Dampener-Rebuild-NBR

Captive Acceleration Tube



[714500](#)

Captive Acceleration Tube


Inlet Filter



[7108.8](#)

Inlet Filter

Flexible Inlet Hose



[990850](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990855](#)

Flexible Discharge Hose