



Model: [7531](#)
Multiple Gun Pressure Unloader

Specs

Max Flow:	21 gpm
Min Pressure:	400 psi
Max Pressure:	2200 psi
Inlet Port Size:	0.5
Discharge Port Size:	0.5
Type of Accessory:	Unloader
Material:	Stainless Steel (S)

Description:

This Stainless Steel Pressure Sensitive Regulating Unloader is designed for single or multiple pump, weep or multi-nozzle systems. This unloader maintains set system pressure and goes into by-pass with the release of the trigger or an obstruction downstream. Pressure is held in the line during by-pass with full pressure when the gun is opened or the obstruction cleared and minimal pressure fluctuation with the alternating use of multiple guns. 5-10% by-pass is necessary for optimum performance.

Accessory to be used with these Pumps:



[101110](#) FRAME PISTON PUMP

[253725](#) FRAME PLUNGER PUMP



[1851](#) OBSOLETE 18 frame plunger pump



[1851K](#) OBSOLETE 18 frame plunger pump



[1051](#)15 FRAME PLUNGER PUMP



[1057](#)15 FRAME PLUNGER PUMP

[1051D](#)15 FRAME PLUNGER PUMP



[82110](#) FRAME PISTON PUMP



[152125](#) FRAME PISTON PUMP



[15315](#) FRAME PLUNGER PUMP



[5CP62215CP](#) PLUNGER PUMP



[7CP6111G1](#) 7CP PUMP WITH GEARBOX

[7CP6171](#) 7CP SS PLUNGER PUMP



[311C5](#) FRAME FLUSHED PLUNGER PUMP



[5CP6221.44101](#)5CP SS PLUNGER PUMP - TEG



[1541.44101](#) 15 FRAME PLUNGER PUMP - TEG



[5CP6241CS.44101](#)5CP SS PLUNGER PUMP - TEG