



Model: [7533](#)
Multiple Gun Pressure Unloader

Specs

Max Flow:	21 gpm
Min Pressure:	800 psi
Max Pressure:	4000 psi
Inlet Port Size:	0.5
Discharge Port Size:	0.5
Type of Accessory:	Unloader
Material:	Stainless Steel (S)

Description:

This Stainless Steel Pressure Sensitive Regulating Unloader is designed for single or multiple pump, weep or multi-nozzle systems. This unloader maintains set system pressure and goes into by-pass with the release of the trigger or an obstruction downstream. Pressure is held in the line during by-pass with full pressure when the gun is opened or the obstruction cleared and minimal pressure fluctuation with the alternating use of multiple guns. 5-10% by-pass is necessary for optimum performance.

Accessory to be used with these Pumps:



[661](#) OBSOLETE 15 frame plunger pump



[381138](#) FRAME BLOCK-STYLE PLUNGER PUMP



[1861K](#)18 FRAME BLOCK-STYLE PLUNGER PUMP



[1861](#) 18 FRAME BLOCK-STYLE PLUNGER PUMP



[6821K68](#) FRAME BLOCK-STYLE PLUNGER PUMP



[3811K38](#) FRAME BLOCK-STYLE PLUNGER PUMP

[351735](#) FRAME PLUNGER PUMP



[3511C35](#) FRAME PLUNGER PUMP

[3511](#)35 FRAME PLUNGER PUMP



[682168](#) FRAME BLOCK-STYLE PLUNGER PUMP



**NO IMAGE
AVAILABLE**

[1051.44101](#)15 FRAME SS PLUNGER PUMP - TEG



[661C](#)15 FRAME PLUNGER PUMP



[661D](#)15 FRAME PLUNGER PUMP